



Model	DZ10010-SS-3Eye
Camera Dimension	350*140*70mm
Lens	3.6-11mm (H.FOV:80°-35°) Electric zoom lens
Sensor	1/1.8" SONY CMOS sensor ,color 0.001Lux F1.2,black/white 0.0001Lux F1.2
Resolution	5MP 2592×1944P 25FPS 4MP 2590×1920P 25FPS 3MP 2048×1536P 25FPS 2MP 1920×1080P 60FPS
Camera housing	316L stainless steel, anti-corrosion
Waterproof level	IP68 (permanent Installed under water)
Water pressure resistance	Maximum 1000Kpa (Waterpressure resisitance 100M)
Buil-in lights	Light sensor contorlled 12 white light ,10 level brightness settings (maximum 4000 lumens) Manual contorlled 12 white light , 10 level brightness settings (maximum 4000 lumens) Light sensor contorlled 8 infrared light ,10 level brightness settings (maximum 4000 lumens) Manual contorlled 8 infrared light ,10 level brightness settings(maximum 4000 lumens)
Image color	Two modes: 1: white light - full color; 2: infrared light - automatic color to black;
Cable	The default length is 20 meters (the longest is no more than 50 meters),PU material,Diameter 7MM.Resistance to 60KG pull,Anti-aging,Anti-friction,Resistance to seawater corrosion,Special underwater wire.
Supporting device	Support iOS, Android, computer, NVR.Compatible with hikvision, dahua, proprietary protocol.(Only support windows-IE browser for camera internal parameter setting)
Supporting agreement	IPv4/IPv6,802.1x,HTTPS, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP,RTSP,ONVIF;SDK Secondary development
Use environment	Sea water / fresh water /Underwater,land,Car,Shipborne.
Working humidity	0%-100%
Working temperature	-20°~55°
Power supply	DC24V 30W
Weight	7kg
Package	1* camera 1* camera bracket 1*U disk (instruction and software)