

D10

- ◆ Model: d10 diving light (haiii)
- ◆ Bulb: cree xp-g r5 led (max 340 lumens)
- ◆ Color temperature: 6500k.
- ◆ Three output levels. High> low>strobe
- ◆ Runtime: high: 110 min, low: 600 min, strobe: 260 min
- ◆ Reflector: glossy aluminum reflector
- ◆ Lens: 8mm polycarbonate board.
- ◆ Body material: durable aircraft-grade aluminum.
- ◆ Angle of light beam 5° hot spot, 110° periphery
- ◆ Surface treatment: premium type iii hard-anodizing.
- ◆ Color: black/grey
- ◆ Battery: cr123 *2 or 18650 li- ion battery *1.
- ◆ With battery over-discharging protection, polarity reversing protection
- ◆ Operation voltage: 3v to 6v.
- ◆ Waterproof: 100 meters underwater
- ◆ Dimensions: 148(length)*23(dia. Of end) *50mm (dia. Of head).
- ◆ Weight: 210 grams (w/o batteries)
- ◆ Operation temperature: -25°C-60°C
- ◆ Impact resistance: 1.5m.
- ◆ Operation instruction: successive switching on-off within two seconds to cycle through high, low, strobe



D33

- ◆ Model: d33 diving light (haiii)
- ◆ Led: three cree xm-l t6 (max 3000 lumens)
- ◆ Color temperature: 6500k
- ◆ Runtime: high: 4.5 hrs low: 9 hrs, strobe: 6 hrs
- ◆ Three output levels, high> low>strobe
- ◆ Reflector: glossy aluminum reflector
- ◆ Lens: 8mm polycarbonate board
- ◆ Body material: durable aircraft-grade aluminum.
- ◆ Angle of light beam 6° hot spot, 50° periphery
- ◆ Surface treatment: premium type iii hard-anodizing.
- ◆ Color: black
- ◆ Battery: 26650 li-ion battery*3.
- ◆ Operation voltage: 8.4v to 10v.
- ◆ Waterproof: 100 meters underwater
- ◆ Dimensions: 295mm (l)*32mm (dia. Of end) *82mm (dia. Of head).
- ◆ Weight: 800 grams (w/o batteries)
- ◆ Operation temperature: -25°C-60°C
- ◆ Impact resistance: 1.5 m.
- ◆ With battery over-discharging protection, polarity reversing protection
- ◆ Operation instruction: successive switching on-off within two seconds to cycle through high, low, strobe

