



# Superstar Global Co., Limited



Email: info@superstar-global.com

Tel: 00852-30606668 / Fax: 00852-31828559

Add: ROOM 1902(A), 19/F., 38 PLAZA, 38 SHAN TUNG STREET MONGKOK, KOWLOON, HONG KONG.

Update Date: 2012-08-15

## Diving flashlight quotation sheet

The product model and pictures		Product basic parameters	
Model	picture	power	function features
UML-300A		<p>[Power]: 3W            [Luminance]: 300LM            [Angle]: 15°            [Distance]: 300m            [Lasting Time]: 90Minutes            [LED]: XP-E R2            [battery]: Single CR123A            [Waterproof Grade]: IPX-8. Waterproof deepness &gt; 100m/330ft            [Size, weight]: D: 30.0mm L: 108mm 100g</p>	<p>1. White light five mode: High Lighting, Medium Lighting, Low Lighting, Strobe Flash, SOS            2. Temperature detection and protection function:            3.: The battery power detection: when batteries electricity shortage, down to 10% brightness            4. The tail metal button to switch control:            5. Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange.</p>
UML-300B		<p>[power]: 3W            [Luminance]: 300LM            [Angle]: 15°            [Distance]: 300m            [Lasting Time]: 90Minutes            [LED]: XP-E R2            [battery]: Single CR123A            [Waterproof Grade]: IPX-8. Waterproof deepness &gt; 100m/330ft            [Size, weight]: D: 30.0mm L: 86.7mm 75g</p>	<p>1. White light five mode: High Lighting, Medium Lighting, Low Lighting, Strobe Flash, SOS            2. Temperature detection and protection function:            3.: The battery power detection: when batteries electricity shortage, down to 10% brightness            4. The tail rotary switch control:            5. Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange.</p>

UML-300E				<p>[power]:3W  [Luminance]:300LM  [Angle]:20°  [Distance]:300m  [Lasting Time]:50Minutes  [LED]:XP-E R2  [battery]:Single 14500  [Waterproof Grade]:IPX-8, Waterproof deepness&gt;100m/330ft  Size, weight]:D:20.0mm L:82.2mm 34g</p>	<ol style="list-style-type: none"> <li>1.The global minimum diving flashlight;</li> <li>2.The tail rotary switch control;</li> <li>3.multicolor</li> </ol>
UML-600A				<p>[power]:5W  [Luminance]:600LM  [Angle]:72°  [Distance]:100m  [Lasting Time]:18650  [LED]:XM-L T6  [battery]:Single18650 Or two CR123A  [Waterproof Grade]:IPX-8, Waterproof deepness&gt;100m/330ft  [Size, weight]:D:34.2mm L:138.5mm 140g</p>	<ol style="list-style-type: none"> <li>1.White light five mode: High Lighting , Medium Lihtina , Low Lihtina , Strobe Flash, SOS</li> <li>2.Temperature detection and protection function;</li> <li>3.: The battery power detection: when batteries electricity shortaae, down to 10% brightness</li> <li>4.Rechargeable batteries and disposable batteries can be interchanged;</li> <li>5.The tail metal button to switch control;</li> <li>6. Fell Outside the adornment circle can choose <u>different color: Red/green/blue/black/orange.</u></li> </ol>
UML-600B				<p>[power]:5W  [Luminance]:600LM  [Angle]:72°  [Distance]:100m  [Lasting Time]:18650  [LED]:XM-L T6  [battery]:Single18650 Or two CR123A  [Waterproof Grade]:IPX-8, Waterproof deepness&gt;100m/330ft  [Size, weight]:D:34.2mm L:118mm 115g</p>	<ol style="list-style-type: none"> <li>1.White light five mode: High Lighting , Medium Lihtina , Low Lihtina , Strobe Flash, SOS;</li> <li>2.Temperature detection and protection function;</li> <li>3.: The battery power detection: when batteries electricity shortaae, down to 10% brightness</li> <li>4.Rechargeable batteries and disposable batteries can be interchanged;</li> <li>5.The tail rotary switch control;</li> <li>6. Fell Outside the adornment circle can choose <u>different color: Red/green/blue/black/orange.</u></li> </ol>
UML-800A				<p>[power]:8W  [Luminance]:800LM  [Angle]:10°  [Distance]:300m  [Lasting Time]:4hours  [LED]:XM-L T6  [battery]:Single26650  [Waterproof Grade ]:IPX-8, Waterproof deepness&gt;100m/330ft  [Size, weight]:D:47.6mm 176.0mm 250g</p>	<ol style="list-style-type: none"> <li>1.White light five mode: High Lighting , Medium Lihtina , Low Lihtina , Strobe Flash, SOS</li> <li>2.Temperature detection and protection function;</li> <li>3.: The battery power detection: when batteries electricity shortaae, down to 10% brightness</li> <li>4.Points level 3 power display:Green (high), blue (Medium), red (low);</li> <li>5.Among tube body metal switch control;</li> <li>6.Fell Outside the adornment circle can choose <u>different color: Red/green/blue/black/orange.</u></li> </ol>

UML-1000A		<p>[power]:10W  [Luminance]:1000LM  [Angle]:72°  [Distance]:100m  [Lasting Time]:80Minutes  [LED]:XM-L T6  [battery]:Single18650  [Waterproof Grade]:IPX-8, Waterproof  deepness&gt;100m/330ft  [Size, weight]:D:34.2mm L:138.5mm 145g</p>	<p>1.White light five mode: High Lighting , Medium Lighting , Low Lighting , Strobe Flash, SOS  2.Temperature detection and protection function;  3.: The battery power detection: when batteries electricity shortage, down to 10% brightness  4.The tail metal button to switch control;</p>
UML-1000N		<p>[power]:10W  [Luminance]:1000LM  [Angle]:20°  [Distance]:100m  [Lasting Time]:80Minutes  [LED]:XM-L T6  [battery]:Single18650  [Waterproof Grade]:IPX-8, Waterproof  deepness&gt;100m/330ft  [Size, weight]:D:28mm L:132.5mm</p>	<p>1.White light five mode: High Lighting , Medium Lighting , Low Lighting , Strobe Flash, SOS.  2.Temperature detection and protection function;  3.The battery power detection: when batteries electricity shortage, down to 10% brightness  4.Points level 3 power display:Green (high), blue (Medium), red (low);  5.Among tube body metal switch control;  6.Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange.</p>
UML-1000W		<p>[power]:10W  [Luminance]:1000LM  [Angle]:70°  [Distance]:100m  [Lasting Time]:80Minutes  [LED]:XM-L T6  [battery]:Single18650  [Waterproof Grade]:IPX-8, Waterproof  deepness&gt;100m/330ft  [Size, weight]:D:36mm L:130.5mm</p>	<p>1.White light five mode: High Lighting , Medium Lighting , Low Lighting , Strobe Flash, SOS.  2.Temperature detection and protection function;  3.The battery power detection: when batteries electricity shortage, down to 11% brightness  4.Points level 4 power display:Green (high), blue (Medium), red (low);  5.Among tube body metal switch control;  6.Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange.</p>
UML-1000WL		<p>[power]:10W  [Luminance]:1000LM  [Angle]:10°  [Distance]:100m  [Lasting Time]:80Minutes  [LED]:XM-L T6  [battery]:Single18650  [Waterproof Grade]:IPX-8, Waterproof  deepness&gt;100m/331ft  [Size, weight]:D:36.2mm L:140.6mm</p>	<p>1. White light has six mode: High Lighting (100%) , Medium Lighting(50%) , Low Lighting (25%) , Strobe Flash(fre:1HZ) , explosion Flash(fre:8HZ),SOS;  2.Temperature detection and protection function;  3、 The battery power detection: When the power of Lithium is lower than the set value, then the control circuit set the LED Brightness down to 5% as  4、 Points level 4 electricity display: blue (high),Green (medium), red (low), red flash (low electrical protection);  5、 Technology patent product.</p>
UML-1000NR		<p>[power]:10W  [Luminance]:1000LM  [Angle]:15°  [Distance]:100m  [Lasting Time]:80Minutes  [LED]:XM-L T6  [battery]:Single18650  [Waterproof Grade]:IPX-8, Waterproof  deepness&gt;100m/332ft  [Size, weight]:D:36.2mm L:140.7mm</p>	<p>1. white light has six mode: High Lighting (100%) , Medium Lighting(50%) , Low Lighting (25%) , Strobe Flash(fre:1HZ) , explosion Flash(fre:9HZ),SOS;  2.Temperature detection and protection function;  3.The battery power detection: When the power of Lithium is lower than the set value, then the control circuit set the LED Brightness down to 6% as Lighting Mode automatically.  4.Points level 5 electricity display: blue (high),Green (medium), red (low), red flash (low electrical protection);  5.Lamp holder with a tail standard camera thread interface (M1/4 "- 20)  6.Technology patent product.</p>

UML-1500W	 	<p>[power]:12W  [Luminance]:1500LM  [Angle]:45°  [Distance]:200m  [Lasting Time]: 1.5 hours  [LED]:XM-L T6*3pcs  [battery]:Single26650  [Waterproof Grade]:IPX-8. Waterproof deepness&gt;100m/330ft  [Size, weight]:D:66mm L:170mm 379g</p>	<p>1.White light five mode: High Lighting , Medium Lightina , Low Lightina , Strobe Flash, SOS  2.Temperature detection and protection function;  3.: The battery power detection: when batteries electricity shortaae, down to 10% brightness  4.Points level 3 power display:Green (high), blue (Medium), red (low);  5.Among tube body metal switch control;  6.Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange.</p>
UML-1500M	 	<p>[power]:Camera Light 12W+Spotlight light 10W+ Green Slaser 20mW  [Luminance]: Camera Light :1500LM  Spotlight light: 1000LM  Green laser:20mW  [Angle]: Camera Light :90°  Spotlight light:15°  [Distance]:200m  [Lasting Time]: Camera Light  Spotlight light: 2  Green laser:&gt;10hour;  [LED]:CREE XP-G/R2*6pcs+XM-L/1PCS+Grenn laser  [battery]:Single26650  [Waterproof Grade]:IPX-8. Waterproof deepness&gt;100m/331ft  [Size, weight]:D:66mm L:170mm</p>	<p>1.Camera Light and Spot light has three mode: High Lightina , Medium Lightina . Low Lightina ;  2.The Camera light has two in hidden mode: Strobe Flash , SOS;  3.The Green laser to has open and close mode;  4.The battery power detection: when batteries electricity shortaae, down to 10% brightness  5.Points level 3 power display:Green (high), blue (Medium), red (low);  6.Among tube body metal switch control;  7.Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange;  8.Temperature detection and protection function;</p>
UML-1500N	 	<p>[power]:12W  [Luminance]:1500LM  [Angle]:15°  [Distance]:200m  [Lasting Time]: 1.5 hours  [LED]:XM-L T6*3pcs  [battery]:Single26650  [Waterproof Grade]:IPX-8. Waterproof deepness&gt;100m/332ft  [Size, weight]:D:66mm L:170mm</p>	<p>1. White light five mode: High Lighting , Medium Lightina , Low Lightina , Strobe Flash, SOS  2.Temperature detection and protection function;  3.The battery power detection: when batteries electricity shortaae, down to 10% brightness  4.Points level 3 power display:Green (high), blue (Medium), red (low);  5.Among tube body metal switch control;  6.Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange.</p>
UML-1500NW	 	<p>[power]:Camera Light 12W+Spotlight light 10W  [Luminance]:Camera Light :1500LM  Spotlight light: 1000LM  [Angle]:Camera Light :90°  Spotlight light:15°  [Distance]:200m  [Lasting Time]: Camera Light  Spotlight light: 2  [LED]:CREE XP-G/R2*6pcs+XM-L/1PCS  [battery]:Single26650  [Waterproof Grade]:IPX-8. Waterproof deepness&gt;100m/333ft  [Size, weight]:D:66mm L:170mm</p>	<p>1.Camera Light and Spot light has three mode: High Lightina , Medium Lightina . Low Lightina ;  2.The Camera light has two in hidden mode: Strobe Flash , SOS;  3.Temperature detection and protection function;  4.The battery power detection: when batteries electricity shortaae, down to 10% brightness  5.Points level 3 power display:Green (high), blue (Medium), red (low);  6.Among tube body metal switch control;  7.Fell Outside the adornment circle can choose different color: Red/green/blue/black/orange;</p>