



Photo	Specification	& Dimension (MM)	Weight Detail (NW / GW) KG
<p>W16S</p>  	<ul style="list-style-type: none"> ◆ Model: W16S Professional Diving Light (HAIII) ◆ Bulb: CREE XM-L U2 LED (Max 860 lumens) ◆ Color temperature: 6500k. ◆ Runtime: High: 90min. ◆ Brightness level: High>OFF ◆ Low-voltage-alarm function: Flash 3 times when the battery voltage lower than 3V, 5seconds later then Switch to 10% low brightness mode automatically Specially designed for diving. ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 4mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 8°. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 18650 Li-ion battery *1. ◆ Battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 3V to 4.5V. ◆ Waterproof: 100 meters underwater ◆ Size: 145 (length)*24 (dia. of end) *29MM (dia. of head) ◆ Weight: 115grams (w/o batteries). ◆ Operation Temperature: -25℃-60℃ ◆ Impact resistance: 1.5 M. ◆ Operation Instruction: Push the switch forward to activate the light. 	<p>Item:148X50(Dia) Inner Box:160x60x60 Carton:380x380x340</p> <p>1 PC/Bubble Bag+Inner Box+(Cardboard) 50pcs/CTN/0.0491'</p> <p>Incl. 18650 battery*1, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	10.5/12.5
<p>W16</p>  	<ul style="list-style-type: none"> ◆ Model: W16 Diving Light (HAIII) ◆ LED: CREE XP-G R5.Max 340 Lumens. ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 110 min, Low: 600 min, Strobe: 260 min ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 5° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: CR123 *2 or 18650 Li- ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 3V to 6V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 148(length)*23(dia. of end)*50mm (dia. of head). ◆ Weight: 210 grams (w/o batteries) ◆ Operation Temperature: -25℃-60℃ ◆ Impact resistance: 1.5M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:144-129x50(Dia) Gift Box:245x175x80 Carton:650x510x370</p> <p>1 PC/Bubble Bag+Inner Box+(Cardboard) 50pcs/CTN/0.0.1226'</p> <p>Incl. 18650 battery*1, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	25.6/27.5
<p>W106W</p>  	<ul style="list-style-type: none"> ◆ Model: W106W Underwater Photographing Light (HAIII) ◆ LED: 100WSWC .Max 10000 Lumens. ◆ Color temperature: 5000k ◆ Max Runtime: 2 hrs. ◆ Three output levels. High>Middle>Low ◆ Reflector: without reflector, for underwater photographing only ◆ Lens: 8mm Polycarbonate Board ◆ Body material: Durable aircraft-grade aluminum ◆ Angle of light beam: 120° ◆ Operation voltage: 18V to 26V. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: Li-ion batteries pack ◆ With battery over-discharging protection, polarity reversing protection ◆ Size: 300(length)*76mm (dia. of head). ◆ Weight: 1772 grams (w/battery and charger) ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, Middle, Low 	<p>Item:300x76(Dia) Gift Box:310x78x78 Carton:380x420x420</p> <p>1 PC/Bubble Bag+Inner Box+(Cardboard) 10pcs/CTN/0.0670'</p> <p>Incl. Battery Pack*1, charger*1, mounting bracket*1, Aluminium Case*1, O-ring*2</p>	30/31
<p>W16U</p>  	<ul style="list-style-type: none"> ◆ Model: W16U zoomable Diving Light/underwater photographing light ◆ Bulb: CREE XM-L U2 LED (Max 680 Lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 70 min, Low: 320 min, Strobe: 150 min ◆ Reflector: Glossy Aluminum reflector ◆ Lens: Aspheric lens. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam: 6°- 68° zoomable ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 18650 Li- ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 2.8V to 4.5V. ◆ Waterproof: 60 meters underwater ◆ Dimensions: 129-144mm (length)*23(dia. of body)*45mm (dia. of head). ◆ Impact resistance: 1.5M. ◆ Weight: 190 grams (without battery); 240 grams (with battery) ◆ Underwater Weight: 200 grams (with battery) ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:144-129x50(Dia) Gift Box:245x175x80 Carton:650x510x370</p> <p>1 PC/Bubble Bag+Inner Box+(Cardboard) 32pcs/CTN/0.0.1226'</p> <p>Incl. 18650 battery*1, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	25.6/27.5
<p>W17V</p> 	<ul style="list-style-type: none"> ◆ Model: W17V Diving Light/underwater photographing light ◆ Bulb: CREE XM-L LED (Max 860 Lumens) ◆ Color temperature: 5000k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 70 min, Low: 320 min, Strobe: 150 min ◆ Reflector:Without reflector,for underwater photographing only ◆ Lens: 4mm Polycarbonate board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam:140° 	<p>Item:125X40(Dia) Gift Box:245x175x80 Carton:650x510x370</p> <p>1 PC/Bubble Bag+Inner</p>	

 <p>ARCHOIT® W17V</p>	<ul style="list-style-type: none"> ◆ Angle of light beam: 110° ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: CR123*2 or 18650 Li-ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 3V to 6V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 125mm (length)*24(dia. of body)*40mm (dia. of head). ◆ Impact resistance: 1.5M. ◆ Weight: 140 grams (without battery); 190 grams (with battery) ◆ Underwater Weight: 95grams (with battery) ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Box+(Cardboard) 32pcs/CTN/0.1226'</p> <p>Incl. 18650 battery*1, charger*1, EVA Case*1, mounting bracket*1, Hand Strap*1 O-ring*2</p>	<p>25.6/27.5</p>
<p>W16XL</p>  <p>ARCHOIT® W16XL</p>	<ul style="list-style-type: none"> ◆ Model: W16XL Diving Light (HAIII) ◆ Bulb: Cree XM-L U2 (Max 860 lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 60min, Low: 320 min, Strobe: 150 min ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 18650 Li-ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 2.8V to 4.5V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 148(length)*23(dia. of end)*50mm (dia. of head). ◆ Weight: 210 grams (w/o batteries) ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:148X50(Dia) Gift Box:245x175x80 Carton:650x510x370</p> <p>1 PC/Bubble Bag+Inner Box+(Cardboard) 32pcs/CTN/0.1226'</p> <p>Incl. 18650 battery*1, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	<p>10.5/12.5</p>
<p>W26</p>  <p>ARCHOIT® W26</p>	<ul style="list-style-type: none"> ◆ Model:W26 Diving Light (HAIII) ◆ LED: Cree XM-L T6 (Max 1000 lumens) ◆ Color temperature: 6500K ◆ Runtime: High: 110 min, Low: 420 min, Strobe: 260min ◆ Three output levels, High>Low>Strobe. ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8MM Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 5.5° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black. ◆ Battery: CR123 *4 or 18650 Li-ion battery *2. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 6V to 10V. ◆ Waterproof: 100 meters underwater ◆ Size: 229(length)*24.5(dia. of end)*60mm (dia. of head) ◆ Weight: 365 grams (w/o batteries) ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5 M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:229x60(Dia) Gift Box:280x200x80 Carton:650x580x420</p> <p>1 PC/Bubble Bag+Inner Box+(Cardboard) 32pcs/CTN/0.0693'</p> <p>Incl. 18650 battery*2, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	<p>18.3/20.3</p>
<p>W28V</p>  <p>ARCHOIT® W28V</p>	<ul style="list-style-type: none"> ◆ Model No.: W28V Underwater Photographing Light (HAIII) ◆ LED: CREE XM-L T6 (Max 1000 lumens) ◆ Color temperature: 5000k. ◆ Runtime: High: 4 hrs Low: 7 hrs, Strobe: 6 hrs ◆ Three brightness levels: High> Low>Strobe. ◆ Reflector: without reflector, for underwater photographing only ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black. ◆ Battery: 26650 Li-ion battery*2. ◆ battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 6V to 10V. ◆ Dimensions: 200mm (length) * 32mm (body diameter) * 60mm (dia. of head). ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5 M. ◆ Weight: 400 g(w/o battery) ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:228x60x32mm Gift Box:300x122x80 Carton:330x280x430</p> <p>1 PC/ gift box Box+ 10pcs/CTN/0.040'</p> <p>Incl. 26650 battery*2, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	<p>13.5/15.5</p>
<p>W28</p>  <p>ARCHOIT® W28</p>	<ul style="list-style-type: none"> ◆ Model: W28 Diving Light (HAIII) ◆ Bulb: CREE XM-L T6 LED (Max 1000 lumens) ◆ Color temperature: 6500k. ◆ Runtime: High: 4 hrs Low: 7 hrs, Strobe: 6hrs. ◆ Three brightness levels, High> Low>Strobe ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 5.5° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 26650 Li-ion battery *2. ◆ Battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 6V to 10V. ◆ Waterproof: 100 meters underwater ◆ Size: 228 (length)*32 (dia. of end) *60MM (dia. of head) ◆ Weight: 365 grams (w/o batteries). ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5 M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:228x60x32mm Gift Box:300x122x80 Carton:330x280x430</p> <p>1 PC/ gift box Box+ 10pcs/CTN/0.040'</p> <p>Incl. 26650 battery*1, charger*1, EVA Case*1, Hand Strap*1, O-ring*2</p>	<p>13.5/15.5</p>
<p>W39</p>  <p>ARCHOIT® W39</p>	<ul style="list-style-type: none"> ◆ Model: W39 Diving Light (HAIII) ◆ LED: Three CREE XM-L T6 (Max 3000 lumens) ◆ Color temperature: 6500K ◆ Runtime: High: 4.5 hrs Low: 9 hrs, Strobe: 6 hrs ◆ Three output levels, High> Low>Strobe ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board 	<p>Item:295x82x32 Gift box:</p>	

 <p>ARCHOIT[®] W39</p> 	<ul style="list-style-type: none"> ◆Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 6° hot spot, 50° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 26650 Li-ion battery*3. ◆ Operation voltage: 8.4V to 10V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 295mm (L)*32mm (dia. of end)*82mm (dia. of head). ◆ Weight: 800 grams (w/o batteries) ◆ Operation Temperature: -25℃-60℃ ◆ Impact resistance: 1.5 M. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>335x170x102 Carton:360x540x370</p> <p>1 PC/ Aluminum Box 10pcs/CTN/0.072'</p> <p>Incl. 26650 battery*3, charger*1, Aluminium Case*1, Hand Strap*1, O-ring*2</p>	<p>15.95/17.9</p>
<p>WH32</p>  <p>ARCHOIT[®] WH32</p>	<p>Model: WH32 Canister Diving Light/Diving Headlight Bulb: CREE XM-L U2 LED Brightness: 1000 Lumens Color temperature: 6500k. Three output levels. High> Low>Strobe Runtime: High: 3.5H, Low:6H, Strobe: 5H Lamp Life: 100000 Hours Reflector: Glossy Aluminum reflector, high temperature industrial processes. Lens: Explosion proof 6mm Polycarbonate Board. Back pressure sealed system Angle of light beam 8° hot spot, 110° periphery Body material: durable aircraft-grade aluminum. Surface treatment: Premium Type III hard-anodized anti-abrasive finish. Color: Black Battery: 26650 Li- ion battery *2 in canister With battery over-discharging protection, polarity reversing protection Operation voltage: 6V to 10V. Waterproof: 100 meters underwater Dimensions: light head: 70mm (length) *46mm (dia. of head); canister: 166mm(length)*36mm (dia. of body) Weight:545 grams (without batteries); 725 grams (with batteries) Underwater Weight: 350 grams (with batteries) Impact resistance: 1.5M.</p>	<p>Light head:70x46mm Canister:166*36 Gift Box:</p> <p>1 PC/ gift box Box+ 10pcs/CTN/0.0730'</p> <p>Incl. 26650 battery*2, Recharger*1, O-ring*2, Aluminium box*1</p>	<p>23.3/25.3</p>
<p>WH31</p>  <p>ARCHOIT[®] WH31</p> 	<ul style="list-style-type: none"> ◆Model: WH31 Canister Diving Light/Diving Headlight ◆Bulb: CREE XM-L U2 LED (Max 1000 Lumens) ◆Color temperature: 6500k. ◆Three output levels. High> Low>Strobe ◆Runtime: High: 210 min, Low: 360 min, Strobe: 300 min ◆Light head: 80° vertical adjustable ◆Reflector: Glossy Aluminum reflector ◆Lens: 6mm Polycarbonate Board. ◆Body material: Durable aircraft-grade aluminum. ◆Angle of light beam 10° hot spot, 110° periphery ◆Surface treatment: Premium Type III hard-anodizing. ◆Color: Black ◆Battery: 26650 Li- ion battery *2 in canister ◆With battery over-discharging protection, polarity reversing protection ◆Operation voltage: 6V to 10V. ◆Waterproof: 100 meters underwater ◆Dimensions: light head: 70mm (length) *46mm (dia. of head); canister: 166(length)*36mm (dia. of body) ◆Weight:513 grams (without batteries); 695 grams (with batteries) ◆Underwater Weight: 360 grams (with batteries) ◆Impact resistance: 1.5M. 	<p>Light head:70x46mm Canister:166*36 Gift Box:</p> <p>1 PC/ gift box Box+ 10pcs/CTN/0.000'</p> <p>Incl. 26650 battery*2, charger*1, EVA case*1, O-ring*2</p>	<p>13.5/15.5</p>
<p>WH36</p>  <p>ARCHOIT[®] WH36</p> 	<ul style="list-style-type: none"> ◆Model: WH36 Canister Diving Light ◆Bulb: CREE XM-L U2 LED*3 (Max 3000 Lumens) ◆Color temperature: 6500k. ◆Three output levels. High> Low>Strobe ◆Runtime: High: 210 min, Low: 420 min, Strobe: 300 min ◆Light head: with handheld bracket ◆Reflector: Glossy Aluminum reflector ◆Lens: 8mm Polycarbonate Board. ◆Body material: Durable aircraft-grade aluminum. ◆Angle of light beam 8° hot spot, 110° periphery ◆Surface treatment: Premium Type III hard-anodizing. ◆Color: Black ◆Battery: 26650 Li- ion battery *3 in canister ◆With battery over-discharging protection, polarity reversing protection ◆Operation voltage: 9V to 14V. ◆Waterproof: 100 meters underwater ◆Dimensions: light head: 84mm (length) *82mm (dia. of head); canister: 233(length)*36mm (dia. of body) ◆Weight:1000 grams (without batteries); 1300 grams (with batteries) ◆Underwater Weight: 710 grams (with batteries) ◆Impact resistance: 1.5M. 	<p>Light head:84x82mm Canister:233*36 Gift Box:</p> <p>1 PC/ gift box Box+ 10pcs/CTN/0.0000'</p> <p>Incl. 26650 battery*3, charger*1, Aluminium case*1, Strap loop*2, Belt*1 O-ring*2</p>	<p>30.3/32.3</p>
<p>W40VR</p>  	<ul style="list-style-type: none"> ◆Model: W40VR multifunction underwater photographing Light ◆Bulb: White CREE XM-L U2 LED *2 (max 2600 Lumens); Red CREE XP-E N3 LED*2 (max 200 Lumens) 6565 LED (max 6W) UV LED (max 6W) ◆Color temperature: White LED: 5700k-7000k; Red LED: 620 nm wavelength 6565 LED:410 nm wavelength;UV LED:365 nm wavelength ◆Runtime: White: 1.2 Hour,Red/Violet/UV:5 Hours ◆Reflector: no hotspot design, no reflector ◆Lens: 4mm Polycarbonate Board. ◆Body material: Durable aircraft-grade aluminum. ◆Angle of light beam: 120° ◆Surface treatment: Premium Type III hard-anodizing. ◆Color: Black ◆Battery: 32650 Li- ion battery *1. ◆With battery over-discharging protection, polarity reversing protection ◆Operation voltage: 2.8V to 4.5V. ◆Waterproof: 100 meters underwater ◆Dimensions: 124.8mm (length)*50mm (dia. of head). ◆Impact resistance: 1.5M. ◆Weight:345 grams (without battery) 483 grams (with battery) ◆Underwater Weight: 220 grams (with battery) ◆Switch mode: Switch 1: red light-purple light- UV light-OFF Switch 2: white light-high-low-SOS-OFF The two switches can be operated separately or simultaneously 	<p>Item:133X60(Dia) Gift Box:245x175x80</p> <p>1 PC/Gift Box+ (Cardboard) 10pcs/CTN/0.000'</p> <p>Incl. 32650 battery*1, charger*1, mounting bracket*1, Giftbox*1, O-ring*2</p>	<p>18.7/20.7</p>
<p>W38VR</p> 	<ul style="list-style-type: none"> ◆Model: W38VR multifunction underwater photographing Light ◆Bulb: White CREE XM-L U2 LED *2 (max 1400 Lumens); Red CREE XP-E N3 		

 <p>ARCHOIT® W38VR</p> 	<p>LED*2 (max 200 Lumens)</p> <ul style="list-style-type: none"> ◆Color temperature: White LED: 5000k; Red LED: 610-630 nm wavelength ◆Three output levels. White high>White low>Red ◆Runtime: High: 90-120min, Low: 240 min, Red:: 210 min ◆Reflector: no hotspot design, no reflector ◆Lens: 6mm Polycarbonate Board. ◆Body material: Durable aircraft-grade aluminum. ◆Angle of light beam: 120° ◆Surface treatment: Premium Type III hard-anodizing. ◆Color: Black ◆Battery: 32650 Li- ion battery *1. ◆With battery over-discharging protection, polarity reversing protection ◆Operation voltage: 2.8V to 4.5V. ◆Waterproof: 100 meters underwater ◆Dimensions: 133mm (length)*28mm (dia. of body)*60mm (dia. of head). ◆Impact resistance: 1.5M. ◆Weight: 290 grams (without battery); 430 grams (with battery) ◆Underwater Weight: 320 grams (with battery) ◆Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, red 	<p>Item:133X60(Dia) Gift Box:245x175x80</p> <p>1 PC/Gift Box+ (Cardboard) 10pcs/CTN/0.000'</p> <p>Incl. 32650 battery*1, charger*1, mounting bracket*1, Giftbox*1, O-ring*2</p>	<p>18.7/20.7</p>
<p>W51</p>  <p>ARCHOIT® W51</p> 	<ul style="list-style-type: none"> ◆Model: W51 Diving Light ◆LED: Five CREE XM-L U2 LED (Max 5000 lumens) ◆Color temperature: 6500K ◆Runtime: High: 3.5 hrs Low: 9 hrs, Strobe: 4 hrs ◆Three output levels, High> Low>Strobe ◆Reflector: Glossy Aluminum reflector ◆Lens: 8mm Polycarbonate Board ◆Body material: Durable aircraft-grade aluminum. ◆Angle of light beam 6° hot spot, 50° periphery ◆Surface treatment: Premium Type III hard-anodizing. ◆Color: Black ◆Battery: 32650 Li-ion battery*4. ◆With battery over-discharging protection, polarity reversing protection ◆Operation voltage: 12V to 17V. ◆Waterproof: 100 meters underwater ◆Dimensions: 377mm (L)*40mm (dia. of body)*104mm (dia. of head). ◆Impact resistance: 1.5 M. ◆Weight: 1600 grams (without batteries); 2100 grams (with batteries) ◆Underwater Weight: 700 grams (with batteries) ◆Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe 	<p>Item:377x104(Dia) Gift box:43x22x13cm</p> <p>1PC / Gift Box+ (Cardboard) 10pcs/CTN/0.000'</p> <p>Incl. 32650 battery*4, charger*2, Aluminium Case*1, Strap*1, O-ring*2</p>	<p>30.8/33.8</p>



MARIN FOTO

KNAPPEN - 5337 RONG

MOBIL: 92023248

INTERNETT: <http://www.marinfo.no>