

Small & light body. Recommended for all underwater digital photographers, even beginners.

DX-1200HD Camera and Housing Set (Black) [00000] O-ring Set [00000]

[Accessories for the 1200HD camera] USB / video cable, lithium-ion battery, battery charger, wrist strap, camera pouch [Accessories for the DX-1200HD housing] LCD monitor hood, hand strap

NEW DX-1200HD Camera and Housing Set

# DX-1200HD



\*The LCD image pictured here is simulated.

## Plenty of optional accessories

The optional Close-UP Lens 125 or Wide-Angle Conversion Lens for DX-860G can be attached/detached even underwater (Close-UP Lens 125 requires the optional Close-UP Lens Ring for DX-1200HD). Using the wide-angle conversion lens, you can get a wider area in the picture even if you get close to the subject. Using the Close-UP Lens 125, you can take pictures with a larger magnification.



## 3-inch LCD monitor – the largest monitor class for compact digital cameras

The 3-inch widescreen LCD monitor allows you to check even the smallest details in the pictures you take and enjoy playing back movies with high definition. By using the LCD monitor hood and inner hood especially designed for the DX-1200HD housing you can further improve the underwater visibility and take pictures while tracking the movements of the subject on the LCD monitor.

The LCD image pictured here is simulated.



## Light and compact for better portability

The basic design was completely revised and the grips were further improved so even beginners can enjoy taking pictures easily. The new design will certainly satisfy the needs of full underwater diving scenes but it also offers portability and ease of use that allow it to be used for marine sports in general and winter sports as well, offering maximum convenience to the photographer.



## Wide-Angle Conversion Lens for DX-860G

[52115]



[Lens] 3 elements in 3 groups  
 [Underwater angle of view] 79° (98° on land)  
 [Magnification] 0.55x  
 [Weight] Approx. 165g / 5.8oz  
 [Dimensions (DIAxD)] 64x42mm / 2.6x1.7inch

This wide-angle conversion lens covers a maximum field angle equivalent to approx. 19.3mm (35mm film camera equivalent) when used with the DX-1200HD.

\*The lens can be used on land, but slight vignetting (dimming) may occur in the four corners of the image. Slightly zoom in to telephoto to eliminate vignetting.

\*When the wide-angle conversion lens is attached, its shadow can appear on the picture if the built-in flash is used. Using an external strobe together with the built-in flash is recommended.



Equivalent to an angle of view of 35mm : value on the land  
 With a standard lens at the wide-angle end



Equivalent to an angle of view of 19.3mm : value on the land  
 With the wide-angle conversion lens for DX-860G at the wide-angle end

High definition CCD – 1/1.72-inch primary color CCD with 12.19 effective megapixels (maximum number of recording pixels 12.43 megapixels) and 3x optical zoom lens (35–102 mm).

Features SEA&SEA mode, a still image mode for optimal underwater photography.

Several White Balance settings available (Auto, Daylight, Cloudy, Fluorescent, Tungsten, Sunset, Custom) to suit any particular scene.

Exposure compensation function (±2EV in 0.5EV steps).

ISO speed can be set up to ISO 3200.

Movie function up to 1280×720 pixels (HD Video) at 30 frames/second (30 fps).

16MB built-in memory. Can record on SD / MMC / SDHC memory cards (up to 8GB).

Specially designed lithium-ion battery and battery charger included.

When you turn the retractable cable socket lever, the fiber-optic cable socket slides and is aligned with position of the built-in flash and fixed.

Flash Light Diffuser function – Effective diffuser that softly diffuses the light of the built-in flash.

Strong and durable build, with a depth rating of up to 45m / 150ft

## Close-UP Lens Ring for DX-1200HD

[00000]

A set-up ring to attach the Close-UP Lens 125 to the DX-1200HD housing



## Spare Battery for 1200HD camera (Standard accessory)

[00000]

## Battery Charger for 1200HD camera (Standard accessory)

[00000]