



Media Release

SUBAL ND800 for Nikon D800

The **SUBAL ND800** is an aluminium housing for the Nikon D800 SLR camera.

The ergonomic placement of all important controls provides convenient and comfortable handling of the camera functions.

The camera is mounted on a saddle for precise positioning inside the housing. A 4 mm main-O-ring and the SUBAL QuickLock system make it virtually impossible to close the housing if the O-ring is not lying correctly in its groove. Maximum security is assured.

Threaded holes in the base of the housing allow for the mounting of trays etc.

A mounting plate with a threaded hole on the top of the housing may be used for a light-weighted aiming light.

Generous shading of the LCD-monitor provides a glare-free view of the brilliant image of the camera monitor.

SUBAL offers 4 different viewfinder systems for this housing:

The **Standard-Viewfinder** reduces the viewfinder image slightly to allow the whole frame to be viewed whilst wearing a diving mask.

The **GS-180** viewfinder and **WS-45** angled viewfinders offer an image size equal to the cameras viewfinder. The GS-180 viewing angle is line of sight and the 360° revolable WS45 is 45°.

The new Prism finder **PS-30** shows the viewfinder image full sized with a viewing angle of 30°. The PS-30 has a long eye relief which is especially helpful for video shooting.

The viewfinder systems are interchangeable and can be mounted easily by the user.

As with all our products choice of materials, machining, surface protection and finish conform with SUBAL's well known standards of reliability and workmanship.

All SUBAL ports with bayonet mount can be fitted to this housing.

Controls:

Power Switch with Display illumination, Shutter Release, Focus/Zoom, Focus Mode Selector, Lens Release Button, Sub Command Dial, Main Command Dial, Mode Dial, Release Mode Dial, Flash Open and Close, AE-Lock/AF-Lock, Metering mode switch, Live View Switch, Movie Record Button, Port Lock.

Push-Buttons for:

Play Back, Delete, Menu, White Balance, ISO, Quality, Lock Release, BKT, Flash Mode, Metering, Exposure Compensation, OK, 2x FN, Multi Selector Buttons, Info, AF-Modus.

Configuration

W – H – D: approx. 270 – 205 – 150mm (w/o Port and Handles)

Weight approx. 3,2 kg with Handles! (w/o Port and Accessories)

Buoyancy: All but neutral (dependant on the port used and accessories)

2 x Sea&Sea Fiber optic Ports

Optional extras:

Up to 3 Bulkheads, Nikonos V, IKELITE or S6 sockets parallel connected

Technical Data

Seawater resistant aluminum alloy, machined from solid, extreme surface hardening and corrosion resistance through HardCoating. 3-layer powder coating. All parts manufactured from anodized and hard coated aluminium, acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings. SUBAL QuickLock latching system.

Strobe arm mount: 2 x T-Plates 25 mm, TLC- or Ultralight base options

Max. depth: 80 m (210 ft), optionally 120m (360 ft)

For inquiries/further information please contact:

SUBAL europe

R. Sempert

Post Box 1607

D-84484 Burghausen

Tel: +49 8677 65897, Fax: +49 8677 65982. e-mail: europe@subal.com

Pictures enclosed