

ARCHON Diving Light / Video Light

Picture	Product Description
<p>1--Diving Flashlight</p>	
	<ul style="list-style-type: none"> ◆ Model: W16 ◆ LED: CREE XP-G R5. Max 340 Lumens. ◆ Color temperature: 6500k. ◆ Three output levels. High > Low > Strobe ◆ Runtime: High: 110 min, Low: 600 min, Strobe: 260 min ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 5° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: CR123 *2 or 18650 Li- ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 3V to 6V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 148(length)*23(dia. of end)*50mm (dia. of head). ◆ Weight: 210 grams (w/o batteries) ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe
	<ul style="list-style-type: none"> ◆ Model: W16XL ◆ Bulb: Cree XM-L U2 (Max 860 lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High > Low > Strobe ◆ Runtime: High: 60min, Low: 320 min, Strobe: 150 min ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 18650 Li- ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 2.8V to 4.5V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 148(length)*23(dia. of end)*50mm (dia. of head). ◆ Weight: 210 grams (w/o batteries) ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe

ARCHON Diving Light / Video Light

Picture	Product Description
	<ul style="list-style-type: none"> ◆ Model No.: V10 ◆ LED: CREE XM-L U2 (Max 860 lumens) ◆ Color Temperature: 6500k ◆ Runtime: High: 2.5 hrs Low: 4.0 hrs, SOS: 3.0hrs ◆ Three Brightness Levels: High(100%)>Low(30%)>SOS>Off ◆ Body Material: Durable Aircraft-grade Aluminum ◆ Angle of Light Beam: 16° ◆ Surface Treatment: Premium Hard-anodizing ◆ Color: Black/ Red/ Blue ◆ Battery: 18650 Battery*1 ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation Voltage: 3V to 4.2V ◆ Waterproof: 60 Meters Underwater ◆ Dimensions: 132mm (Length) * 28mm (Dia. of Head) ◆ Impact Resistance: 1.5 M ◆ Weight: 105 Grams (Without Batteries); 138 Grams (With Batteries) ◆ Underwater Weight: 65 Grams (With Batteries)
	<ul style="list-style-type: none"> ◆ Model: W26 ◆ LED: Cree XM-L T6 (Max 1000 lumens) ◆ Color temperature: 6500K ◆ Runtime: High: 110 min, Low: 420 min, Strobe: 260min ◆ Three output levels, High>Low>Strobe. ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8MM Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 5.5° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black. ◆ Battery: CR123 *4 or 18650 Li- ion battery *2. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 6V to 10V. ◆ Waterproof: 100 meters underwater ◆ Size: 229(length)*24.5(dia. of end)*60mm (dia. of head) ◆ Weight: 365 grams (w/o batteries) ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5 M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe

ARCHON Diving Light / Video Light

Picture	Product Description
 <p>The image shows the ARCHON W28 diving light, a black cylindrical device with a textured head and a lens. Below it is an open carrying case containing the light, two batteries, and other accessories.</p>	<ul style="list-style-type: none"> ◆ Model: W28 ◆ Bulb: CREE XM-L T6 LED (Max 1000 lumens) ◆ Color temperature: 6500k. ◆ Runtime: High: 4 hrs Low: 7 hrs, Strobe: 6hrs. ◆ Three brightness levels, High> Low>Strobe ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 5.5° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 26650 Li-ion battery *2. ◆ Battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 6V to 10V. ◆ Waterproof: 100 meters underwater ◆ Size: 228 (length)*32 (dia. of end) *60MM (dia. of head) ◆ Weight: 365 grams (w/o batteries). ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5 M. ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe
 <p>The image shows the ARCHON W39 diving light, a black cylindrical device with a textured head and a lens. Below it is an open carrying case containing the light, three batteries, and other accessories.</p>	<ul style="list-style-type: none"> ◆ Model: W39 ◆ LED: Three CREE XM-L T6 (Max 3000 lumens) ◆ Color temperature: 6500K ◆ Runtime: High: 4.5 hrs Low: 9 hrs, Strobe: 6 hrs ◆ Three output levels, High> Low>Strobe ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 6° hot spot, 50° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 26650 Li-ion battery*3. ◆ Operation voltage: 8.4V to 10V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 295mm (L)*32mm (dia. of end)*82mm (dia. of head). ◆ Weight: 800 grams (w/o batteries) ◆ Operation Temperature: -25°C-60°C ◆ Impact resistance: 1.5 M. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, strobe

ARCHON Diving Light / Video Light

Picture	Product Description
	<ul style="list-style-type: none"> ◆ Model: W16S ◆ Bulb: Cree XM-L U2 ◆ Brightness: 860 lumens ◆ Color temperature: 6500k. ◆ Mode: high-OFF ◆ Runtime: 1.5h ◆ Lamp Life: 100000 Hours ◆ Lens: 4mm Polycarbonate Board. ◆ Reflector: Glossy Aluminum reflector, high temperature industrial processes. ◆ Body material: durable aircraft-grade aluminum alloy. ◆ Surface treatment: Premium Type III hard-anodized anti-abrasive finish. ◆ Color: Black ◆ Battery: 18650 Li- ion battery *1. <p>With battery over-discharging protection, polarity reversing protection</p> <ul style="list-style-type: none"> ◆ Operation voltage: 3V to 4.5V. ◆ Water resistant deepness: 100 meters underwater ◆ Construction: Shakeproof and waterproof ◆ Dimensions: 145(length)*24(dia. of body)*29mm (dia. of head). ◆ Weight: 115 g (w/o batteries) ◆ Impact resistance: 1.5M.

2--Canister Diving Light

	<ul style="list-style-type: none"> ◆ Model: WH31 Diving Headlight ◆ Bulb: CREE XM-L U2 LED (Max 1000 Lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High > Low > Strobe ◆ Runtime: High: 210 min, Low: 360 min, Strobe: 300 min ◆ Light head: 80° vertical adjustable ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 6mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 10° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 26650 Li- ion battery *2 in canister <p>◆ With battery over-discharging protection, polarity reversing protection</p> <ul style="list-style-type: none"> ◆ Operation voltage: 6V to 10V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: light head: 70mm (length) *46mm (dia. of head); canister: 166(length)*36mm (dia. of body) ◆ Weight: 513 grams (without batteries); 695 grams (with batteries) ◆ Underwater Weight: 360 grams (with batteries) ◆ Impact resistance: 1.5M.
--	---

ARCHON Diving Light / Video Light

Picture	Product Description
 <p>The image shows the ARCHON WH32 diving light, which is a black cylindrical device with a lens at the front and a handle at the back. It is connected to a black cable. Below the light is its carrying case, which is black with orange accents and is open, showing the light and other accessories inside.</p>	<ul style="list-style-type: none"> ◆ Model: WH32 ◆ Bulb: CREE XM-L U2 LED ◆ Brightness: 1000 Lumens ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 3H, Low:6H, Strobe:4H ◆ Lamp Life: 100000 Hours ◆ Reflector: Glossy Aluminum reflector, high temperature industrial processes. ◆ Lens: Explosion proof 6mm Polycarbonate Board. ◆ Back pressure sealed system ◆ Angle of light beam 8° hot spot, 110° periphery ◆ Body material: durable aircraft-grade aluminum. ◆ Surface treatment: Premium Type III hard-anodized anti-abrasive finish. ◆ Color: Black ◆ Battery: 26650 Li- ion battery *2 in canister ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 6V to 10V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: light head: 70mm (length) *46mm (dia. of head); canister: 166mm(length)*36mm (dia. of body) ◆ Weight:545 grams (without batteries); 725 grams (with batteries) ◆ Underwater Weight: 350 grams (with batteries) ◆ Impact resistance: 1.5M.

 <p>The image shows the ARCHON WH36 diving light, which is a black cylindrical device with a lens at the front and a handle at the back. It is connected to a black cable. Below the light is its carrying case, which is black with orange accents and is open, showing the light and other accessories inside.</p>	<ul style="list-style-type: none"> ◆ Model: WH36 ◆ Bulb: CREE XM-L U2 LED*3 (Max 3000 Lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 210 min, Low: 420 min, Strobe: 300 min ◆ Light head: with handheld bracket ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 8° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 26650 Li- ion battery *3 in canister ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 9V to 14V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: light head: 84mm (length) *82mm (dia. of head); canister: 233(length)*36mm (dia. of body) ◆ Weight:1000 grams (without batteries); 1300 grams (with batteries) ◆ Underwater Weight: 710 grams (with batteries) ◆ Impact resistance: 1.5M.
--	--

ARCHON Diving Light / Video Light

Picture	Product Description
	<ul style="list-style-type: none"> ◆ Model: WH46 (two heads optional) ◆ Bulb: CREE XM-L U2 LED*4 (Max 4000 Lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 5.0h, Low: 15.0h, Strobe: 8.0h ◆ Light head: with handheld bracket ◆ Reflector: Glossy Aluminum reflector ◆ Lens: 8mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam 8° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: rechargeable Li-ion battery pack (26650 battery *8) ◆ Battery Indicator: 100%-50%: Green; 50%-30%: Yellow; 30%-10%: Red; Below 10%: Red Flashing; Below 5%: switch off; ◆ Can be charged directly on the light, with battery over-discharging protection, polarity reversing protection ◆ Fully charging time: 8-10h; ◆ With gas release valves ◆ Operation voltage: 12V to 18V; ◆ Waterproof: 200 meters underwater ◆ Dimensions: 244.5mm (canister length)* 78.2mm (dia. Of canister) * 64.5mm (dia. Of light head); ◆ Weight: 2420 grams (with battery pack) ◆ Underwater Weight: 1150 grams (with battery pack) ◆ Impact resistance: 1.5M.
	<ul style="list-style-type: none"> ◆ Model: WG96 ◆ Bulb: SST-90 LED *1 (max 2200 Lumens); ◆ Modes: High> Low>Strobe> off ◆ Runtime: : High (3.0h); Low(8.0h); Strobe (4.0h); ◆ Color temperature: 6000K; ◆ Reflector: Glossy Aluminum reflector; ◆ Lens: 8mm Polycarbonate Board; ◆ Body material: Durable aircraft-grade aluminum; ◆ Angle of light beam: 8° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing; ◆ Color: Black ◆ Battery: Rechargeable Li- ion battery pack (18650 battery*6); ◆ Battery Indicator: 100%-50%: Green; 50%-30%: Yellow; 30%-10%: Red; Below 10%: Red Flashing; Below 5%: switch off; ◆ Can be charged directly on the light, with battery over-discharging protection, polarity reversing protection ◆ Fully charging time: 8-10h; ◆ With gas release valves; ◆ Operation voltage: 9V to 13V; ◆ Waterproof: 200 meters underwater ◆ Dimensions: 213.5mm (length)* 78.0mm (dia. of head); ◆ Weight: 1300 grams (with battery pack) ◆ Underwater Weight: 640 grams (with battery pack) ◆ Impact resistance: 1.5M

ARCHON Diving Light / Video Light

Picture	Product Description
	▼ Impact resistance: 1.5M.

 	<ul style="list-style-type: none"> ◆ Model: WG66 ◆ Bulb: White CREE XM-L2 U2 LED *6 (max 5000 Lumens); ◆ Modes: High> Low>Strobe> off ◆ Runtime: : High (2.0h); Low(4.0h); Strobe (3.0h); ◆ Color temperature: 6500K; ◆ Reflector: Glossy Aluminum reflector; ◆ Lens: 8mm Polycarbonate Board; ◆ Body material: Durable aircraft-grade aluminum; ◆ Angle of light beam: 8° hot spot, 110° periphery ◆ Surface treatment: Premium Type III hard-anodizing; ◆ Color: Black ◆ Battery: Rechargeable Li- ion battery pack (18650 battery*6); ◆ Battery Indicator: 100%-50%: Green; 50%-30%: Yellow; 30%-10%: Red; Below 10%: Red Flashing; Below 5%: switch off; ◆ Can be charged directly on the light, with battery over-discharging protection, polarity reversing protection ◆ Fully charging time: 8-10h; ◆ With gas release valves ◆ Operation voltage: 9V to 13V; ◆ Waterproof: 200 meters underwater ◆ Dimensions: 213.5mm (length)* 78.0mm (dia. of head); ◆ Weight: 1187grams (with battery pack) ◆ Underwater Weight: 585 grams (with battery pack) ◆ Impact resistance: 1.5M.
--	--


4. Diving Light for Video and photographing

 	<ul style="list-style-type: none"> ◆ Model: W17V ◆ Bulb: CREE XM-L LED (Max 680 Lumens) ◆ Color temperature: 5000k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 70 min, Low: 320 min, Strobe: 150 min ◆ Reflector: Without reflector ◆ Lens: Aspheric lens. ◆ Angle of light beam: 110° ◆ Body material: durable aircraft-grade aluminum. ◆ Surface treatment: Premium Type III hard-anodized anti-abrasive finish. ◆ Color: Black ◆ Battery: 18650 Li- ion battery *1 or CR123. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 3V to 6V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 125mm (length)*24(dia. of body)*40mm (dia. of head). ◆ Impact resistance: 1.5M. ◆ Construction: Shakeproof and waterproof. ◆ Weight: 190 grams (without battery) ◆ Underwater Weight: 95 grams (with battery)
---	--

ARCHON Diving Light / Video Light

Picture	Product Description
---------	---------------------

 <p>The image shows the ARCHON W40VR diving light, a black cylindrical device with a lens and a handle. Below it is the carrying case, which is black with orange trim and contains the light, a battery, and some documentation.</p>	<ul style="list-style-type: none"> ◆ Model: W40VR ◆ Bulb: white light: CREE XML2 U2 (second generation)x 4 Red light: CREE XP-E N3 x 2 wavelength: 620 nm Purple light x 2 wavelength: 410nm UV X2 wavelength: 365 nm ◆ Color temperature: 5000K—5500K (white light) ◆ Brightness: white light: 2600lumens Red light: 200lumens Purple light: 6W UV light: 6W ◆ Switch mode: switch 1: red light-purple light- UV light-OFF ◆ Switch 2: white light-high-low-SOS-OFF ◆ Both of two switch can be lighted at the same time. ◆ Runtime: White light High mode: 1.2H ◆ Red/purple/UV light: 5H ◆ Light angle: 120° ◆ Lens: 4mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 32650 rechargeable Li- ion battery x1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 2.8V to 4.5V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 124.8mm(length)* 50mm (dia. of head). ◆ Weight: 345grams (without battery); 483 grams (with battery) ◆ Underwater Weight: 220 grams (with battery) ◆ Impact resistance: 1.5M.
--	--

 <p>The image shows the ARCHON W42VR diving light, a black cylindrical device with a lens and a handle, similar in design to the W40VR model.</p>	<ul style="list-style-type: none"> ◆ Model: W42VR ◆ Bulb: White CREE XM-L2 U2 LED *8 (max 5200 Lumens); Red CREE XP-E N3 LED*4 wavelength 620 nm (max 400 Lumens); Purple LED *2 wavelength 410nm (max 6W); UV LED*2 wavelength 365nm (max 6W); ◆ Switch 1: Red> Purple> UV> off ◆ Switch 2: White high> White medium >White low> off ◆ The two switches can be operated separately or simultaneously. ◆ Runtime: White High Mode: 1.5H; White Medium Mode: 3.0H; White Low Mode: 4.0H Red Light: 4.0H; Purple Light: 5.0H; UV light: 5.0H ◆ Color temperature: 5000K (white light) ◆ Reflector: No hotspot design, no reflector; ◆ Lens: 4mm Polycarbonate Board; ◆ Body material: Durable aircraft-grade aluminum; ◆ Angle of light beam: 120°
--	---

ARCHON Diving Light / Video Light

Picture	Product Description
	<ul style="list-style-type: none"> ◆ Angle of light beam: 120° ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 18650 rechargeable Li- ion battery *4; ◆ Battery Indicator: 100%-50%: Green; 50%-30%: Yellow; 30%-10%: Red; Below 10%: Red Flashing; Below 5%: switch off; ◆ With battery over-discharging protection, polarity reversing protection ◆ with gas release valves ◆ Operation voltage: 2.8V to 4.2; ◆ Waterproof: 100 meters underwater ◆ Dimensions: 140.9mm (length)* 62.6mm (dia. of head); ◆ Weight: 490 grams (without battery); 682.4 grams (with battery) ◆ Underwater Weight: 330 grams (with battery) ◆ Impact resistance: 1.5M.


	<ul style="list-style-type: none"> ◆ Model: W38VR ◆ Bulb: White Cree XM-L U2 LED *2 (max 1400 Lumens); Red Cree XP-E N3 LED*2 (max 200 Lumens) ◆ Color temperature: White LED: 5000k; Red LED: 610-630 nm wavelength ◆ Three output levels. White high>White low>Red ◆ Runtime: High: 90-120min, Low: 240 min, Red:: 210 min ◆ Reflector: no hotspot design, no reflector ◆ Lens: 6mm Polycarbonate Board. ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam: 120° ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 32650 Li- ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 2.8V to 4.5V. ◆ Waterproof: 100 meters underwater ◆ Dimensions: 133mm (length)*28mm (dia. of body)*60mm (dia. of head). ◆ Impact resistance: 1.5M. ◆ Weight: 290 grams (without battery); 430 grams (with battery) ◆ Underwater Weight: 320 grams (with battery) ◆ Operation Instruction: Successive switching ON-OFF within two seconds to cycle through high, low, red


ARCHON Diving Light / Video Light

Picture	Product Description
	<ul style="list-style-type: none"> ◆ Model: W16U (zoomable) ◆ Bulb: CREE XM-L U2 LED (Max 680 Lumens) ◆ Color temperature: 6500k. ◆ Three output levels. High> Low>Strobe ◆ Runtime: High: 70 min, Low: 320 min, Strobe: 150 min ◆ Reflector: Glossy Aluminum reflector ◆ Lens: Aspheric lens ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam: 6°-68°. ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: 18650 Li- ion battery *1. ◆ With battery over-discharging protection, polarity reversing protection ◆ Operation voltage: 2.8V to 4.5V. ◆ Waterproof: 60 meters underwater ◆ Dimensions: 144-129mm(length)*23(dia. of end)*50mm (dia. of head). ◆ Weight: 200 grams (w/o batteries);240 grams with battery. ◆ Impact resistance: 1.5M.

	<ul style="list-style-type: none"> ◆ Model: WG76W ◆ Bulb: White CREE XM-L2 U2 LED *12 (max 6500 Lumens); CREE XP-E N3*4 (wavelength 620nm, max 400 Lumens) ◆ Modes: High>Medium> Low>Red> off ◆ Runtime: : High (1.5h); Medium (3.0h); Low (5.0h); Red (8.0h) ◆ Color temperature: 5000K (white light); ◆ Reflector: No hotspot design, no reflector; ◆ Lens: 5mm Polycarbonate Board; ◆ Body material: Durable aircraft-grade aluminum; ◆ Angle of light beam: 120° ◆ Surface treatment: Premium Type III hard-anodizing; ◆ Color: Black ◆ Battery: Rechargeable Li- ion battery pack (18650 battery*6); ◆ Battery Indicator: 100%-50%: Green; 50%-30%: Yellow; 30%-10%: Red; Below 10%: Red Flashing; Below 5%: switch off; ◆ Can be charged directly on the light, with battery over-discharging protection, polarity reversing protection. ◆ Fully charging time: 8-10h; ◆ With gas release valves ◆ Operation voltage: 9V to 13V; ◆ Waterproof: 200 meters underwater ◆ Dimensions: 213.5mm (length)* 78.0mm (dia. of head); ◆ Weight: 1140 grams (with battery pack)
--	--

ARCHON Diving Light / Video Light


Picture	Product Description
	<ul style="list-style-type: none"> ◆ Underwater Weight: 560 grams (with battery pack) ◆ Impact resistance: 1.5M.

	<ul style="list-style-type: none"> ◆ Model: WH166 ◆ Bulb: White CREE XM-L2 U2 LED *8 (max 5500 Lumens); CREE XP-E N3*4 (wavelength 620nm, max 400 Lumens) ◆ Modes: High>Medium> Low>Red> off ◆ Runtime: : High (1.5h); Medium (3.0h); Low (5.0h); Red (8.0h) ◆ Color temperature: 5000K (white light); ◆ Reflector: No hotspot design, no reflector; ◆ Lens: 5mm Polycarbonate Board; ◆ Light head: with handheld bracket ◆ Body material: Durable aircraft-grade aluminum. ◆ Angle of light beam : 120°; ◆ Surface treatment: Premium Type III hard-anodizing. ◆ Color: Black ◆ Battery: rechargeable Li-ion battery pack (26650 battery *8) ◆ Battery Indicator: 100%-50%: Green; 50%-30%: Yellow; 30%-10%: Red; Below 10%: Red Flashing; Below 5%: switch off; ◆ Can be charged directly on the light, with battery over-discharging protection, polarity reversing protection ◆ Fully charging time: 8-10h; ◆ With gas release valves ◆ Operation voltage: 12V to 18V; ◆ Waterproof: 200 meters underwater ◆ Dimensions: 244.5mm (canister length)* 78.2mm (dia. Of canister) * 56.5mm (dia. Of light head); ◆ Weight: 2230 grams (with battery pack) ◆ Underwater Weight: 1100 grams (with battery pack) ◆ Impact resistance: 1.5M.
---	---

WH46 light head set

	
<p>WH166 light head set</p>	

ARCHON Diving Light / Video Light

Picture	Product Description
 The image shows the ARCHON Diving Light / Video Light and its accessories. The main unit is a black, cylindrical light with a textured front lens and a mounting bracket. A black cable with a coiled section is attached to the back. Below the main unit are two additional components: a small black cap and a black mounting bracket with a silver screw.	

—



—

—

—

—

—

—

—

—

—

—

—

—

—

—

—

—

—

—

—

—